



First choice when  
quality counts.™

# PRO™ Accessories

## Accessories for PRO Guns: PRO 3500sc™, PRO 3500hc™, PRO 4500sc™, PRO AA4500™

### Push/Pull Fan Air Valve Kit

**224-883** PRO 3500sc, PRO 3500hc,  
PRO 3500wb

**224-720** PRO 4500sc & PRO AA4500

This kit allows the operator to change the standard rotary style fan air control valve on the gun to a linear push/pull design. It has settable stops at either end of the valve to allow two preset fan patterns. Rotary control is still maintained.

### 4-Finger Trigger Kit

**223-054** PRO 3500sc, PRO 3500hc

**224-884** PRO 4500sc

**236-163** PRO AA4500

This kit allows you to change the gun from a standard 2-Finger Trigger operation to a 4-Finger Trigger.

### Air-Reducing Valve

**238-927** PRO 3500sc, PRO 3500hc,  
PRO 3500wb, PRO 4500sc

This valve is used to control the amount of air that goes to the air cap of the gun. It also allows full operation of the fan control on airspray guns.

### 112-534 Airline Quick Disconnect Swivel (with Airline Shutoff)

Allows quick installation and removal of guns, and improves mobility for better painter comfort. The male section of this quick disconnect replaces the gun air inlet fitting. The female section fits on the lefthand end of the standard air hose. The hose end has a check shut-off built in.

### 223-976 E/S On/Off Conversion Kit

This kit replaces the turbine on/off switch and locks the valve in the on position. A ball valve replaces the gun air inlet fitting which has the special lefthand threads at its inlet. This allows the total air to be turned off during cleaning or color-changing, while insuring that the E/S air stays on during operation.

### 185-493 Air Hose Adaptor Nipple

This adaptor allows for the connection of multiple air hose as needed for the special grounded PRO air holes. 1/4 npsm(L.H.) x 1/4 npsm.

### 218-374 Box of 10 Gun Covers

Designed to fit over the PRO guns to help keep the gun free of overspray and paint residue. The elastic holds these gun covers tightly to the gun barrel, just behind the air cap. The back has a snap closure to allow access to gun controls. Greatly reduces gun cleaning and operator cleaning time.

### 105-749 Cleaning Brush

A non-plastic end type brush for cleaning air caps and guns. Not affected by solvents.

### 222-011 Ground Clamp

Clamp (universal) with 25 ft. (7.6 m) of heavy wire to ground objects in the spray booth.

### 110-090 Snap Ring Pliers

Used for removing the E/S On/Off Valve for service.

### 236-129 Air Swivel Fitting (non Quick Disconnect)

Replaces gun inlet fitting. 360° swivel to provide improved operator mobility and comfort.

### Gun Inlet Filter

**915-921** PRO 3500sc, PRO 3500hc,  
PRO 4500

100 mesh filter at gun fluid inlet.

### 235-300 Gun Mounting Bracket

Allows gun to hang with barrel in a downward orientation to prevent material from getting into the air passages.

## Accessories for PRO 3500 Only

### 223-451 High Conductivity Kit

Provides the necessary parts to convert a PRO 3500sc to a PRO 3500hc.

### 223-780 High Conductive Solvent Hose Kit

When highly conductive solvents are used, this 25 ft. (7.6 m) hose improves electrostatic performance with higher tip voltages by reducing current loss to ground through the fluid line. This hose can handle material down to 2 megohm • cm.

## Accessories for PRO 4500 and PRO AA4500 (Full Featured)

### 224-388 Spraying Voltage Readout

This receiving device provides a digital readout of the spraying voltage of PRO 4500 and PRO AA4500 guns equipped with voltage transmission capability.

## Accessories for PRO AA4500

### Fluid Filter

**238-563** 60 mesh, 3-pak  
**238-564** 60 mesh, 25-pak  
**238-561** 100 mesh, 3-pak  
**205-262** 100 mesh, 25-pak

These elements fit into the fluid filter in the fluid inlet fitting of the PRO AA4500.

### 189-018 Fluid Inlet Swivel

This swivel fits between the gun and the fluid line to allow a swivel action, thus aiding in gun maneuverability and operator comfort (3000 psig capable with 1/4 npsm x 1/4 npsf).

### Flexible Nylon Static-Free, Whip, Fluid Hose

**236-134** 3 ft. (0.9 m)

**236-135** 6 ft. (1.8 m)

3000 psi (200 bar), 1/8 in. ID, 1/4 npsf swivel x 1/4 npsm

### PRO AA4500 Only:

#### Flexible Conductive, Whip, Air Hose

**236-130** 3 ft. (0.9 m)

**236-131** 6 ft. (1.8 m)

3/16 in. ID, 1/4 npsm (L.H.) Swivel x 1/4 npsm (L.H.). PRO conductive air hose, metallic ground. Use on PRO AA4500 only – air restriction is too great for air spray gun use.