

PowrTwin XLT FEATURES

The Contractor's Choice for Big Projects!

PowrTwin™ XLT

When Reliability Counts!



Speeflo is the world's most popular manufacturer of hydraulic paint sprayers.

PowrTwin XLT models are perfect for interior and exterior work. They convert quickly from petrol to electric and are easy for one person to transport to the job and on the job. PowrTwins are powerful enough to spray the most difficult architectural and commercial coatings.

*Proven reliable and easy to maintain...
Speeflo is the only sprayer you will ever need!*

1 HydraDrive™

- Mechanical valve eliminates expensive electronic switching devices.
- External Hydraulic Fluid Porting with new and upgraded fittings, allow for quick trouble shooting and easy maintenance.
- Precision rod alignment for maximum chrome life.
- SAE O-Ring fitting for precision alignment.

2 Converts from Petrol to Electric

- Change from petrol to electric or vice versa in seconds – without tools. Never miss a job because you don't have the right power. Use the petrol engine on exteriors or switch to electric for inside jobs. **Your PowrTwin keeps your crew on the job making you money.**

230 V Convertokit



Honda Engine



120 V Convertokit

3



Hydraulic Fill and Dip Stick

- Easy access equals less mess
- Sturdy metal dip stick

4



High Capacity Hydraulic Fluid Cartridge Filter

- Keeps hydraulic system clean and easy to maintain

5



Heavy Duty Paint Filter

- Longer tip life
- Increased productivity



6 Coolflo™ Hydraulic Pump

- Runs cool
- No clutch to wear
- No routine maintenance

7 Hydraulic Fluid Reservoir

- Compact and lightweight for maximum portability and heat dissipation



XLT DI Models Direct Immersion

	PowrTwin™ 6900XLT DI	PowrTwin™ 12000XLT DI
Petrol Model Bare	N/A	N/A
Electric Model Bare, 110-120 V, 1.5 kW (2 hp) Extended Life-DC	N/A	N/A
Electric 230 V Model w/ S-5 Gun, Tip, and 3/8" Hose Kit & Heavy Duty Bypass Valve	448-370	N/A
Petrol Model w/ S-5 Gun, Tip, and 3/8" Hose Kit	N/A	459-355
Petrol Model w/ S-5 Gun, Tip, and 3/8" Hose Kit & Heavy Duty Bypass Valve	448-360	N/A
Petrol Engine	4 kW (5.5 hp) Honda	7 kW (9 hp) Honda
Max. Tip Size - Petrol	1 gun - 1.22 mm (.048")	1 gun - 1.47 mm (.058")
<i>Maximum tip sizes vary with materials sprayed</i>	2 guns - .84 mm (.033") 3 guns - .58mm (.023") 4 guns - .48 mm (.019")	2 guns - 1.02 mm (.040") 3 guns - .86 mm (.034") 4 guns - .76 mm (.030") 5 guns - .66 mm (.026") 6 guns - .61 mm (.024")
Max. Tip Size - Electric	1 gun - .91 mm (.036") 2 guns - .66 mm (.026") 3 guns - .48 mm (.019")	1 gun - .91 mm (.036") 2 guns - .66 mm (.026") 3 guns - .48 mm (.019")
Max. Output - Petrol	8.14 lpm (2.15 gpm)	11.9 lpm (3.15 gpm)
Max. Output - Electric	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)
Max. Operating Pressure	228 bar (3,300 psi)	228 bar (3,300 psi)
Cycles Per Liter	14 L (55 gal)	10 L (40 gal)
Paint Outlet Filter	5 mesh	5 mesh
Filter Area	115 cm ² (18 in ²)	115 cm ² (18 in ²)
Frame	EZ-Load Swing-In	EZ-Load Swing-In
Sprayer Dimensions	109 cm H x 69 cm W x 89 cm L 43" (L) x 27" (W) x 35" (H)	117 cm H x 69 cm W x 89 cm L 46" (L) x 27" (W) x 35" (H)
Sprayer Weight - Petrol	67.6 kgs (149 lbs)	85.3 kgs (188 lbs)
Sprayer Weight - Electric	74.8 kgs (165 lbs)	87.1 kgs (192 lbs)
Honda Petrol Convertokit	506-275	506-277
Exl-DC Electric Convertokit 110-120 V	506-279	506-279
DC Electric Convertokit 230 V	506-251	506-251

The PowrTwin XLT DI series are designed specifically for airless spray fillers. These extremely powerful machines are also ideal for spraying latex, solvent and emulsion paints.





XLT Models Siphon Hose Feed

	PowrTwin™ 4900XLT	PowrTwin™ 6900XLT	PowrTwin™ 8900XLT	PowrTwin™ 12000XLT
Petrol Model Bare	335-305	448-305	449-305	N/A
Electric Model Bare, 110-120 V, 1.5 kW (2 hp) Ext. Life-DC	335-310	448-310	N/A	459-310
Electric 230 V Model w/ LX-80° Gun, Tip, and 1/4" Hose Kit	335-325	448-325	N/A	N/A
Petrol Model w/ LX-80° Gun, Tip, and 1/4" Hose Kit	335-315	448-315	N/A	N/A
Petrol Model w/ S-5 Gun, Tip, and 1/4" Hose Kit	N/A	N/A	N/A	459-315
Petrol Engine	3 kW (4 hp) Honda	4 kW (5.5 hp) Honda	5 kW (6.5 hp) Honda	7 kW (9 hp) Honda
Electric Motor	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC
Max. Tip Size - Petrol	1 gun - .91 mm (.036")	1 gun - 1.22 mm (.048")	1 gun - 1.32 mm (.052")	1 gun - 1.47 mm (.058")
<i>Maximum tip sizes vary with materials sprayed</i>	2 guns - .71 mm (.028")	2 guns - .84 mm (.033")	2 guns - .97 mm (.038")	2 guns - 1.02 mm (.040")
	3 guns - .56 mm (.022")	3 guns - .58 mm (.023")	3 guns - .81 mm (.032")	3 guns - .86 mm (.034")
		4 guns - .48 mm (.019")	4 guns - .71 mm (.028")	4 guns - .76 mm (.030")
			5 guns - .61 mm (.024")	5 guns - .66 mm (.026")
				6 guns - .61 mm (.024")
Max. Tip Size - Electric	1 gun - .78 mm (.031")	1 gun - .91 mm (.036")	1 gun - .91 mm (.036")	1 gun - .91 mm (.036")
	2 guns - .58 mm (.023")	2 guns - .66 mm (.026")	2 guns - .66 mm (.026")	2 guns - .66 mm (.026")
	3 guns - .48 mm (.019")	3 guns - .48 mm (.019")	3 guns - .48 mm (.019")	3 guns - .48 mm (.019")
Max. Output - Petrol	4.73 lpm (1.25 gpm)	8.14 lpm (2.15 gpm)	8.9 lpm (2.35 gpm)	11.9 lpm (3.15 gpm)
Max. Output - Electric	4.16 lpm (1.10 gpm)	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)
Max. Operating Pressure	228 bar (3,300 psi)	228 bar (3,300 psi)	228 bar (3,300 psi)	228 bar (3,300 psi)
Cycles Per Liter	23 L (87 gal)	14 L (55 gal)	10 L (40 gal)	10 L (40 gal)
Paint Outlet Filter	50 mesh	50 mesh	50 mesh	50 mesh
Filter Area	115 cm² (18 in²)	115 cm² (18 in²)	115 cm² (18 in²)	115 cm² (18 in²)
Frame	EZ-Load Compact	EZ-Load Compact	EZ-Load H.D.	EZ-Load H.D.
Sprayer Dimensions	94 cm H x 69 cm W x 89 cm L 37" (L) x 27" (W) x 35" (H)	94 cm H x 69 cm W x 89 cm L 37" (L) x 27" (W) x 35" (H)	109 cm H x 69 cm W x 89 cm L 43" (L) x 27" (W) x 35" (H)	117 cm H x 69 cm W x 89 cm L 46" (L) x 27" (W) x 35" (H)
Sprayer Weight - Petrol	59 kgs (130 lbs)	63.1 kgs (139 lbs)	70.3 kgs (155 lbs)	82.6 kgs (182 lbs)
Sprayer Weight - Electric	63.1 kgs (139 lbs)	67.1 kgs (148 lbs)	74.4 kgs (164 lbs)	85.3 kgs (188 lbs)
Honda Petrol Convertokit	506-112	506-275	506-278	506-277
ExI-DC Electric Convertokit 110-120 V	506-217	506-211	506-276	506-207
DC Electric Convertokit 230 V	506-252	506-251	506-251	506-251



The PowrTwin XLT series are designed for large building projects. They have the ability to use multiple guns from one PowrTwin XLT sprayer.





Accutrol™ Pressure Control

- Accurate from 28 bar up to 227 bar
- No electronics
- No freeze hazard
- No maintenance



High Efficiency Cooling Fan

- Keeps the hydraulics cooler for longer life



Durable, Chrome Plated Cart

- Telescoping handle and lift handle for easy loading

Large Pneumatic Tyres

- Large pneumatic tyres for ease of transportation, even in the most severe job-site conditions

Foot Valve

- Submersed lower foot valve allows for siphoning of ultra heavy coatings and knockdown textures (PowrTwin 6900DI only).



EZ-Swing Frame

- Allows for less spillage during paint changes
- Lowers height of unit for easier transportation

ACCESSORIES



SYNERGY
FINE-FINISH TIP

Product No. 671-XXX



WIDESPRAY™

Product No. 661-XXXX

- The Longest Lasting Tip in the Industry.
- Universal size to fit most bases.
- Fewer passes and better coverage than competitors because of full fan pattern with minimal feathering.
- New one-piece seal and retainer.

Product No. 661-XXX

SC-6 Reversible Tip Guard	661-012
S5 Gun w/SC-6 Tip	550-100
S3 Gun w/SC-6 Tip	550-250
L70 Inline Gun	550-475
LX-80 th Gun w/SC-6 Tip	580-100
Reel-EZ 16 - 406 mm (16") Hose Reel	769-100
Reel-EZ 10 - 254 mm (10") Hose Reel	769-200
LX 75 Ploe Gun 120 cm (47.2")	550-495
Tip Extension 15 cm (6") 7/8 THD	651-070
Tip Extension 30 cm (12") 7/8 THD	651-071
Tip Extension 45 cm (18") 7/8 THD	651-072
Tip Extension 61 cm (24") 7/8 THD	651-073
Tip Extension 15 cm (6") 11/16 THD	651-121
Tip Extension 30 cm (12") 11/16 THD	651-122
Tip Extension 45 cm (18") 11/16 THD	651-123
Tip Extension 61 cm (24") 11/16 THD	651-124
90 cm (3') Extension Pole w/Swivel Head, 7/8 Nut	310-390
180 cm (6') Extension Pole w/Swivel Head, 7/8 Nut	310-391
Gun Extension Swivel Head, 7/8	651-139
Gun Extension Swivel Head, 11/16	651-140

Spray/Roll Application Kit	310-110
229 mm (9") Telescoping Pressure Roller Kit	310-950
6.35 mm (1/4") x 15.2 m (50') Airless Hose, 228 bar	316-505
4.76 mm (3/16") x .91 m (3') Airless Whip Hose	550-240
Fine Mesh Gun Filter (Pack of 2)	500-200-10
Medium Mesh Gun Filter (Pack of 2)	500-200-06
Coarse Mesh 440i Manifold Filter (Pack of 2)	500-200-03
Medium Mesh 640i Manifold Filter	730-067
Inlet Screen for STD PowrTwins	103-627
Manifold Filter Mastic - 0 Mesh	930-004
Manifold Filter Mastic - 5 Mesh	930-005
Manifold Filter Mastic - 50 Mesh	930-006
Manifold Filter Mastic - 100 Mesh	930-007
Large Inlet Screen (Rock Catcher) DI	710-046
3.175 mm (1/8") Airless Tip Gaskets (12 Gaskets)	711-612
Piston Lube - 237 mL (8 oz.) Bottle	314-480
Piston Lube - 118 mL (4 oz.) Bottle	314-481
LS-10 Liquid Shield Plus - .95 L (1 Qt.) Bottle	314-482
LS-10 Liquid Shield Plus - 118 mL (4 oz.) Bottle	314-483

Imported by:

Distributed by:

International Sales

Titan Tool, Inc.

107 Bauer Drive

Oakland, NJ 07436

Tel: +201 337 1240

Fax: +201 405 7449

Website: www.titantool.com/international

Ask for Genuine Titan/Speedflo Parts and Accessories



Global Leader in Paint
Spray Technology



Convertible Petrol/Electric Airless Paint Sprayers



PowerTwinTM XLT Series



When Reliability Counts!



*Global Leader in Paint
Spray Technology*